

RG725 Commissioning Instructions

Requirements

- RG725
- SIM Card
- Flat Head Screwdriver

The device should be in its default factory state. If not please follow **Internal RG725 Default Instructions** process

SIM Insertion

1. Unscrew rear cover
2. Remove rear cover
3. Remove battery
4. Slide SIM card into SIM1 slot
5. Note SIM, Serial and IMEI 1 numbers
6. Replace battery
7. Replace rear cover
8. Screw in rear cover

Initial Device Setup from Default

1. Press and hold power button (above PTT)
2. Complete Google Setup Wizard as follows
 - a. Select Language then click Start
 - b. Select Wi-Fi network and enter password
 - c. Click Connect
 - d. Select Set up as new
 - e. Select Skip to bypass Google sign in
 - f. Select Skip again
 - g. Name the device
 - h. Click Next
 - i. Choose Not Now on Protect Phone
 - j. Click Skip Anyway
 - k. Location set to On
 - l. Improved Location set to On
 - m. Send System data set to Off
 - n. Click Accept
 - o. Click No Thanks

SIM Setup

1. Open Settings
2. Select Network and Internet
 - a. Click Mobile Network
 - b. Turn Data Roaming On
 - c. Select preferred network type as 4G
 - d. Click Access point names

Wireless Logic SIM

- i. Click "+" icon
- ii. Set name to Wlapn.com
- iii. Set APM to Wlapn.com
- iv. Set Username/Password to Airsys
- v. Click three dots icon and Save

SIM Setup Cont.

Jola SIM

- i. Click + icon
- ii. Set name to globaldata.iot
- iii. Set APN to globaldata.iot
- iv. Click three dots icon and Save
- e. Select new APN
- f. Enhanced 4G LTE Mode set to On
- g. Select Network operators
- h. Choose network provider
- i. Select Data usage
 - i. Mobile data set to On
- j. Select SIM cards
 - i. Ensure SIM slot 1 is on
- k. Click the back button

Device Settings

1. Select Display
 - a. Select Sleep
 - i. Choose desired time limit
 - b. Click Advanced
 - ii. Auto-rotate set to Off
 - c. Click back button
2. Select Security & Location
 - a. Select Privacy
 - iii. Set Location to Device only
 - b. Click the back button
3. Select System
 - a. Select Date & Time
 - i. Auto Date & Time
 - ii. Select Use network-provided
 - iii. Auto time zone set to On
 - iv. Use 24-hour format set to On

Airsys.Cloud Application (.apk) Download

1. Open Chrome browser
2. Go to <https://www.airsys.cloud>
 - a. Click 3 bars icon (top right)
 - b. Select Downloads
 - c. Select Software
 - d. Pick A.Flex Smart Mobile APP or A.Flex PTT Mobile APP (use dependant)
 - e. The app will download

Airsys.Cloud Application (.apk) Install

1. Once download open Files from App Drawer
 - a. Select Downloads
 - b. Select the Airsys.Cloud application
 - c. Choose Install
 - d. The app will be installed on the device
 - e. Once installed click Done

Airsys.Cloud Application (.apk) Login

User credentials required from this point. Follow User Setup process to obtain.

1. Open the Airsys.Cloud App from the home screen
2. Select No to Send collected data for improvement when prompted
3. Select Yes to Allow save password

Then

1. Select QR code reader icon (bottom left)
2. Scan supplied QR code
3. Click Connect

Or

1. Click the gear icon (bottom middle)
 - a. Insert Username and click OK (variable)
 - b. Insert Password and click OK (variable)
 - c. Insert Server and click OK (002.airsys.cloud permanent)
 - d. Insert Port and click OK (Variable)
 - e. Autostart set to On
 - f. Autologin set to On
 - g. Event sounds set to On
 - h. Use HW intents set to On
 - i. Click Select HW intents
 - i. PTT set to On
 - ii. SOS set to On
 - iii. Channel Change set to On
 - iv. Channel Change reverse order set to On
 - v. Click back button
 - j. Click the back button
 - k. Click Connect

Final Device Setup

1. Go to Settings
 - a. Select Network & Internet
 - i. Set Wi-Fi to Off
 - b. Select Connected Devices
 - i. Set Bluetooth to Off
2. If Installed open Custom Key Application
 - a. Assign PTT button
 - b. If not installed, then
 - i. Connect device to PC
 - ii. Load Custom Key .apk into device
 - iii. Open Files
 - iv. Locate Custom Key .apk
 - v. Select Install Custom Key .apk
 - vi. Once installed open Custom Key .apk
 - vii. Assign PTT button